

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A motorcycle ~~tire having tire, comprising:~~
a plurality of main blocks scattered on a ~~tread, tread;~~ tread; and ~~characterized in that~~
sub blocks ~~are provided between the main blocks, said each~~ sub block being
made of rubber and having block height lower than that of the main ~~block, and blocks,~~
wherein a part of the rubber constituting a top portion of the sub block ~~has~~
~~been~~ is removed to reduce the area of a upper face of the sub block.
2. (Currently Amended) The motorcycle tire according to claim 1, ~~characterized~~
~~in that wherein~~ said sub blocks are positioned between the main blocks adjacent with each
other in ~~the tire's~~ a tire width direction.
3. (Currently Amended) The motorcycle tire according to claim 1, ~~characterized~~
~~in that wherein~~ said sub blocks are positioned between the main blocks adjacent with each
other in ~~the tire's~~ a tire circumferential direction.
4. (Currently Amended) The motorcycle tire according to claim 1, ~~characterized~~
~~in that wherein~~ said sub blocks are positioned between the main blocks adjacent with each
other in ~~the~~ a direction slanted in relation to ~~the tire's~~ a tire circumferential direction.
5. (Currently Amended) The motorcycle tire according to claim 1, ~~characterized~~
~~in that wherein the~~ a negative ratio is between 65 % and ~~97 %;~~ 97%, the negative ratio being
an amount of space of the grooves, calculated as a percentage of the tread area in each of
plural basic pattern elements, on condition that the upper face area of the top portion of the
sub block is included in the groove;

a tread curvature ~~ratio- ratio~~, obtained when a distance measured along the ~~tire's a tire~~ radial direction between a tire sectional height position and a tread edge position is divided by the tread ~~width- width~~, is between 0.20 and 0.50;

a block area ~~ratio- ratio~~, defined as the ratio of total area of upper faces of top portions of the sub blocks to a total area of upper faces of the main ~~blocks- blocks~~, is between 0.05 and 1.2 in each of plural basic pattern elements constituting the tread; and

a block height ~~ratio- ratio~~, defined as a ratio of a block height of the sub blocks at its ~~an~~ upper face to a block height of the main ~~blocks- blocks~~, is between 0.3 and 0.8.

6. (Currently Amended) The motorcycle tire according to claim 5, ~~characterized in that~~wherein said negative ratio is between 75 % and 97 %, said tread curvature ratio is between 0.20 and 0.50, and said block area ratio is between 0.2 and 1.2.

7. (Currently Amended) The motorcycle tire according to claim 5, ~~characterized in that~~wherein said negative ratio is between 65 % and 85 %, said tread curvature ratio is between 0.20 and 0.50, and said block area ratio is between 0.05 and 0.5.

8. (Currently Amended) The motorcycle tire according to claim 1, ~~characterized in that when~~wherein a bending portion is provided at a mid point of a side wall extending from a groove bottom toward ~~the an~~ upper face of ~~the a~~ sub block and the sub block is divided into a bottom portion and a top portion, and the upper face area of the top portion is between 0.2 and 0.8 times as much as the upper face area of the bottom portion.

9. (Currently Amended) The motorcycle tire according to claim 1, ~~characterized in that~~wherein a bending portion is provided at a mid point of a side wall extending from a groove bottom toward an upper face of the sub block, and the height of said bending portion from the groove bottom along ~~the tire's a tire~~ radial direction is at least 0.5 times and less than 1.0 times as much as the block height of the sub block.

10. (Currently Amended) The motorcycle tire according to claim 1, ~~characterized in that~~wherein said sub block has such a shape that a dimension in ~~the tire's~~a tire circumferential direction is greater than a dimension in ~~the tire's~~a tire width direction.

11. (Currently Amended) The motorcycle tire according to claim 1, ~~characterized in that~~wherein said tire has a radial carcass.

12. (New) The motorcycle tire according to claim 1, wherein the upper face of at least one sub block comprises at least one chamfered edge.

13. (New) The motorcycle tire according to claim 1, wherein the central region of the upper face of at least one sub block comprises a depression.